



NOTES:

- 1) INPUT - 115 VOLTS 60 HZ STANDARD. ALSO AVAILABLE 230 VOLTS AND 50 HZ.
- 2) DISPLAY USES RED LIGHT EMITTING DIODES.
- 3) COLONS - DISPLAYS FURNISHED WITH COLONS WHICH FLASH AT 1 HZ RATE.
- 4) PM INDICATOR - 12 HOUR DISPLAY ONLY HAS PM TIME INDICATOR GIVEN BY DOT.
- 5) POWER FAILURE INDICATION - INDICATED BY ENTIRE DISPLAY FLASHING AT 1 HZ RATE. PUSHING FAST OR SLOW SET CONTROLS CANCELS THIS INDICATION.
- 6) PANEL FINISH - MATTE BLACK

2 3/4"H x 4 9/16"W
UNPAINTED ALUM.
COVER

REV: E	REV. DATE: 11/4/04	REV. BY: DGC
DATE: 3/7/1977	 company, inc medfield, ma	
DRAWN BY: JPL		
CHECKED BY: ~	TITLE: PDC-8412-BLK & PDC-8424-BLK	
	SUBJECT: 0.84" DIGITAL PANEL MOUNT - BLK	
	DWG SIZE: A	DWG NO: A-3298
PATH: M:\INVENTOR\DRAWINGS\A-3298.IDW		

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN OR INVENTION ARE RESERVED.