

INDOOR CLOCKS

STYLE 5000 & 2000 AVAILABLE IN **ROUND & SQUARE DESIGNS IN** SIZES FROM 9" TO 24".


Style 5000 (round) and 2000 (square) clocks are available in standard sizes from 9" to 24" in either surface. semi-flush, or double-faced versions.

INDOOR STYLE HR50924 CLOCK.

shown with standard hands, dial markings and case. The "HR" specifies the clock face, hands and finish, the 50924 specifies the clock to be surface mounted 24" in diameter

INDOOR SIDE-WALL MOUNTED

STYLE G53924 Clock, shown with standard hands, dial markings and case. The "G" specifies the clock face, hands and finish, the 53924 specifies the clock to be double faced, 24" in diameter.



Black Dial White Dial

Χ

*X

Χ

Χ

R

R

R

R

N/A

R

16 7/8"

3 1/4"

22916

R

X: indicates standard style R: indicates reversed screening

* indicates black on white dial

Styles & Finishes

Astro - Style E

Attache - Style M Big H - Style H

Clarendon - Style T

Gemini - Style D

Monitor - Style G

Patriot - Style F

Solaris - Style S

Urbanite - Style K





STANDARD SPECIFICATIONS:

Case: aluminum - round, aluminum - square

Crystal: 12"-24" flat glass. (9" Convex glass) - Acrylic or polycarbonate crystals optionally available

Movement: Standard - 115 Volts. 60 Hertz synchronous movement. All brass gear train. Battery - Quartz battery movement optionally available on clocks through 16" by specifying the suffix QB after the clock style number.

Wall Box: WB8 Wall box furnished as standard for semiflush designs, round & square clocks. WB5CS wall box furnished standard in Double-faced clocks through 16".

Finishes: Refer to table for standard finishes. Custom finishes available upon request. Contact the factory for details

Hands: Refer to table for standard hands. Custom hands or any of the hand designs as shown throughout our catalog. Contact the factory for details

Dials: Made of metal as shown. Any of the dial styles as shown on this page can be specified by placing the dial style prefix in front of the clock style number.

Weatherproof: Weatherproof designs available in the 12" through 24" round surface mounting clocks. Specify the prefix "WP" before the clock style number.

X/R

X/R

X/R

DOUBLE-FACED

X/R

Χ

Χ

Χ

Χ

Χ

R

R

R

X/R









Monitor Style GR



X/R

X/R

X/R



Style F

Patriot Style FR





Urbanite

Style KR

Round Round Round 9" *5009 9 3/4" 3 1/4" *5209 **1 1/8" *5309 7 3/8" 9 11/32" 10" 12 5/s" 12" 50912 12 5/8" 3 1/4" 52912 12 21/64" 1 15/16" 53912 12 15/16" 15 ⁹/₁₆ ' 15 5/8" 1 15/16" 15" 50915 52915 15 15/16" 15 15/16" 18 9/16" 3 3/8" 53915 7 5/8" 52918 19" 3" 18" 50918 19" 4 9/16" 53918 19 23" 8 1/2" 24" 50924 25 5/16" 4 9/16" 52924 25 5/16" 3" 53924 25 5/16" 29 5/16" 8 1/211 Square Square 1 15/16" 12" 20912 12 1/4" 3 1/4" 22912 12 1/4" 23912 12 9/16" 15 9/16" 7 3/8"

16 ⁷/₈"

1 15/16

23916

17 1/4"

20 1/4"

7 3/。"

SEMI-FLUSH

Χ

- * Clocks are provided standard with a convex alass crystal
- f If QB movement case depth is 1 15/16".



16"

20916